



- NOTES:
1. REF. PCD # 741024-103 COMPLIES WITH PCD REQ. BY SIMILARITY
  2. STATEMENT THAT PART TESTED PER MIL-T-641 AND FUNGICIDE INSULATORS TO JAX TESTED PER MIL-T-641 AND FUNGICIDE INSULATORS.
  3. MATES WITH "SWITCHCRAFT INC." # 482 "LITTEL" PLUG OR WE 310
  4. OPERATING TEMP -65° TO +230°F.
  5. INSULATION CONTACT RESISTANCE & DIELECTRIC SHALL MEET MIL-J-641 FSC # 82389
  6. WEIGHT - .08 POUNDS MAX. (INCLUDES HARDWARE)

SIZE	WIDTH	MULT.	TEMPER.	FINISH	PER FINISH SPEC. NO.	PART NO.	ISSUE
	LOG. PER M					27 1784 A	A

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT, INC. AND IS RELEASED ON A COMPROMISED BASIS FOR IDENTIFICATION PURPOSE ONLY. UNLESS OTHERWISE SPECIFIED:

1. DECIMAL DIMENSIONS & .000
2. FRACTIONAL DIMENSIONS & 1/64
3. ANGLES ± .01°
4. ALL DIM'S CONSIDERING VARIATION AND TOL.
5. FOR THROUGH HOLES UNLESS SHOWN OTHERWISE
6. REMOVE ALL BURRS.
7. PART TO BE FABRICATED AS SPECIFIED. MAKE NO DIMENSIONAL ADJUSTMENTS FOR APPLIED FINISHES, I.E. PLATING, PAINTING, ETC.
8. HOLES ON SAME CENTERLINE MUST BE IDENTIFIED, DIMENSIONED & TOL.
9. DO NOT SCALE DRAWING

DRAWN BY: R.O. DATE: 8-31-71

CHECKED BY: W.D. DATE: 9-3-71

APPROVED BY: W.C. DATE: 9-9-71

PER MAT. SPEC. NO. \_\_\_\_\_

FINISH \_\_\_\_\_

PER FINISH SPEC. NO. \_\_\_\_\_

PER MAT. SPEC. NO. \_\_\_\_\_

SWITCHCRAFT

PART NO. 27 1784 A

ISSUE A

18 - 100300 5 5 4 2 9 915