

Search By Catalog Number

[Home](#) > [Terminal Blocks](#) > [Barrier - Double Row](#) > 603 GP Series - Double Row Terminal Blocks

603 GP Series - Double Row Terminal Blocks

**603 GP 06**

Specifications

- A Kulka® Brand
- 50 amps
- 600 Volts AC/DC, Class B/C
- Base, phenolic, 150°C (UL RTI)
- JJ (GDI-30F) material available
- Screws, steel, #10-32 phil-slot
- Terminals, plated brass
- Open back design (Insulator strip required for voltage rating - **Reference**)
- 1-12 poles at 11/16" centers
- Accepts lugs w/max width of .47"
- Bare wire range #10-#16 AWG

Standards

- UL recognized file no. XCFR2.E47811
- CSA certified file no. LR19766
- CE Compliant (IEC 60947-7-1)
- RoHS compliant

Datasheets

[603 GP Standard](#)[603 GP Mod](#)[603 JJ](#)[603 GP 2302](#)

Double Row Terminal Blocks - 603 GP Series

Catalog #	# of Poles	Dimensions	
		A	B
603 GP 01	1	1.81	1.38
603 GP 02	2	2.50	2.06
603 GP 03	3	3.19	2.75
603 GP 04	4	3.88	3.44
603 GP 05	5	4.56	4.12
603 GP 06	6	5.25	4.81
603 GP 07	7	5.94	5.50
603 GP 08	8	6.62	6.19
603 GP 09	9	7.31	6.88
603 GP 10	10	8.00	7.56
603 GP 11	11	8.68	8.25
603 GP 12	12	9.37	8.94

mm = dim X 25.4

Hardware Options

(Hardware options may affect ratings - Consult Customer Service)

Catalog #	Product Description	Reference Sheet
KT67	Full Quick Connect (0 degree Flat)	Reference
KT68	Full Quick Connect (45 degree Bend)	
KT69	Full Quick Connect (90 degree Bend)	
KT64	Half Quick Connect (0 degree Flat)	
KT65	Half Quick Connect (45 degree Flat)	
KT66	Half Quick Connect (90 degree Flat)	
Y	Feed Thru Solder (.60)	Reference
J 603	Line-to-Line Jumper	Reference
2302	Stud	Reference
PSB	Phil-Slot Brass Screw	Consult Customer Service

Quick Connects: .032" x .250"

