

EXAMPLES OF APPLICATION-SPECIFIC DESIGNS

Pendant Switch

Remote hand held pushbutton switch with coiled cord that extends to approximately 3'.

Circuit: SPNO-DB
Rating: 10 amps Resistive @ 28VDC
Button: Black nylon
Housing: Black nylon
Cord: Black polyurethane, 28 AWG
U2-098



Coiled Cord Switch

Remote hand held pushbutton switch with 72" coiled cord. Sealed against dust and moisture.

Rating: 10 amps Resistive @ 28VDC
Button: Green nylon
Housing: Black anodized aluminum
Cable: 6' extended, 18 AWG
P3-80012



Grip Switch Assembly

Switch is built into a grip designed for rugged outdoor use. Automotive type connector.

Circuit: SPNC-DB
Rating: 10 amps Resistive @ 28VDC
Button: Red nylon
Housing: Black nylon
Cord: Black polyurethane, 18 AWG
Left and right hand operation with various connection types available.
U2-076



Pendant Switch

Remote hand held pushbutton switch with 24" coiled cord that extends to approximately 15'. Terminated with a 1/4" right angle molded phone plug (optional).

Circuit: SPNO-DB
Rating: 5 amps Resistive @ 28VDC
Button: Black nylon
Housing: Black nylon
Cord: Black polyurethane, 22 AWG
U2-034



Pendant Switch

Remote hand held pushbutton switch with 7.0" +/- 1.0" wire leads.

Circuit: SPST Alternate Action
Rating: 5 amps Resistive @ 28VDC
Button: Red nylon
Housing: Black nylon
Cord: Black polyurethane, 18 AWG
U2-150



Pendant Switch

Remote hand held pushbutton switch with coiled cord that extends to approximately 20'. Terminated with a connector.

Circuit: SPNO-DB
Rating: 5 amps Resistive @ 28VDC
Button: Red nylon
Housing: Black nylon
Cord: Black neoprene, 18 AWG
Connector: Deutsch
U2-096

