

## General Information

<b>Extended Product Type:</b>	ZS16-PE
<b>Product ID:</b>	1SNK510150R0000
<b>EAN:</b>	3472595101504
<b>Catalog Description:</b>	ZS16-PE Screw Clamp Terminal Block - Ground - Green/Yellow
<b>Long Description:</b>	Improve the safety of your installation in the event of a short-circuit thanks to our screwless rail contact: - Rail contact non operator dependent, - Performances above the requirements of IEC 60947-7-2 terminal block standard, - Secured snap on or remove from the rail, - PE.N function available by combining ZS16-PE with ZS16-BL and 2 poles jumper bar JB10-2.

## Ordering

<b>Color:</b>	Green-Yellow
<b>Minimum Order Quantity:</b>	20 piece
<b>Customs Tariff Number:</b>	85369010

## Popular Downloads

<b>Data Sheet, Technical Information:</b>	1SNK161018D0201
<b>Instructions and Manuals:</b>	1SNK160027C0201

## Dimensions

<b>Product Net Width:</b>	10 mm
<b>Product Net Height:</b>	60.6 mm
<b>Product Net Length:</b>	48.8 mm
<b>Product Net Depth / Length:</b>	48.8 mm
<b>Product Net Weight:</b>	32 g

## Technical

<b>Rated Cross-Section:</b>	16 mm <sup>2</sup>
<b>Spacing:</b>	10 mm
<b>Connection Type:</b>	Screw clamp
<b>Function:</b>	Ground
<b>Number of Levels:</b>	1
<b>Connecting Capacity Main Circuit:</b>	Screw Clamp / Flexible 1x 0.5 ... 16 mm <sup>2</sup> Screw Clamp / Rigid 1x 0.5 ... 16 mm <sup>2</sup> Screw Clamp / With Insulated Ferrule 1x 0.5 ... 10 mm <sup>2</sup> Screw Clamp / Without Insulated Ferrule 1x 0.5 ... 16 mm <sup>2</sup>

<b>Gauge Type:</b>	A6-B6
<b>Rated Short-time Withstand Current (<math>I_{cw}</math>):</b>	for 1 s 1920 A
<b>Rated Impulse Withstand Voltage (<math>U_{imp}</math>):</b>	8000 V
<b>Dielectric Test Voltage:</b>	2200 V
<b>Pollution Degree:</b>	3
<b>Degree of Protection:</b>	acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
<b>Insulation Material:</b>	Polyamide
<b>Mounting on DIN Rail:</b>	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
<b>Wire Stripping Length:</b>	13.5 mm
<b>Recommended Screw Driver:</b>	5.5 mm

## Technical UL/CSA

<b>Connecting Capacity Main Circuit UL/CSA:</b>	Screw Clamp / Flexible 1x 24 ... 4 AWG Screw Clamp / Rigid 1x 24 ... 4 AWG Screw Clamp / With Insulated Ferrule 1x 24 ... 8 AWG Screw Clamp / Without Insulated Ferrule 1x 24 ... 4 AWG
<b>Connecting Capacity UL/CSA:</b>	Stranded 4 AWG
<b>Flammability According to UL94:</b>	V0

## Environmental

<b>Ambient Air Temperature:</b>	Operation -55 ... +110 °C Storage -55 ... +110 °C
<b>Resistance to Vibrations acc. to IEC 60068-2-6:</b>	Compliant
<b>RoHS Status:</b>	Following EU Directive 2002/95/EC August 18, 2005 and amendment

## Certificates and Declarations (Document Number)

<b>ATEX Certificate:</b>	1SND162004A1708
<b>BV Certificate:</b>	1SND161073A0204
<b>CB Certificate:</b>	1SND161022A0201
<b>CSA Certificate:</b>	1SND161070A0209
<b>cUL Certificate:</b>	1SND161040A0206
<b>Declaration of Conformity - CE:</b>	1SND225112U1004
<b>DNV Certificate:</b>	1SND161087A0202
<b>EAC Certificate:</b>	1SND161010A1100
<b>Environmental Information:</b>	1SND220071E1000
<b>Instructions and Manuals:</b>	1SNK160027C0201
<b>RINA Certificate:</b>	1SND161088A0200

**RMRS Certificate:** 1SND161008A1101

**RoHS Information:** 1SND230491F0206

## Classifications

**Object Classification Code:** X

**E-nummer:** 2925977

**ETIM 4:** EC000901 - Ground terminal block

**ETIM 5:** EC000901 - Ground terminal block

**ETIM 6:** EC000901 - Ground terminal block

## Container Information

**Package Level 1 Units:** 20 piece

**Package Level 1 Width:** 101 mm

**Package Level 1 Depth / Length:** 120 mm

**Package Level 1 Height:** 50 mm

**Package Level 1 Gross Weight:** 0.64 kg

**Package Level 1 EAN:** 3472595101504

**Package Level 2 Units:** 160 piece

**Package Level 2 Width:** 200 mm

**Package Level 2 Depth / Length:** 300 mm

**Package Level 2 Height:** 200 mm

**Package Level 2 Gross Weight:** 5.12 kg

**Package Level 3 Units:** 15360 piece

**Product Packing Type:** Box

