



- NOTES**
- ENCLOSURE FINISHED WITH GREEN EPOXY BASED ENAMEL COLOR NO. 34151 PER FEDERAL STANDARD 595
 - SWITCH SEALED PER MIL-PRF-8805 SYMBOL 4
 - TO ADJUST ROLLER DIRECTION REMOVE ROLLER GUIDE LOCK RING, SCREW ROLLER GUIDE DOWN AS FAR AS POSSIBLE, THEN UNSCREW TO DESIRED DIRECTION. SECURE BY REPLACING ROLLER GUIDE LOCK RING
 - CIRCUIT DIAGRAM AND CATALOG LISTING ARE SHOWN ON NAMEPLATE
 - FURNISHED UNASSEMBLED WITH EACH UNIT
 - COINCIDENCE OF OPERATING AND RELEASING POINTS: .010 OF PLUNGER TRAVEL
 - HARDWARE MAY BE PACKAGED UNASSEMBLED PER MIL-PRF-8805
 - UNDER LABORATORY TESTING, THIS CATALOG LISTING HAS DEMONSTRATED CAPABILITY IN CONTROLLING A 120VAC, 60HZ, 2A. INDUCTIVE LOAD FOR 25,000 CYCLES. TESTING WAS CONDUCTED PER MIL-PRF-8805 CONDITIONS AND LOADS PER PARAGRAPH 4.7.30.

CATALOG LISTING
21EN76-R1
PAGE 1 OF 1
ISSUE **23**
CMH
23MAR10
RELEASE NO. SR-9360
REPLACES
REVISIONS
A 0093092
4 JUN 98
B 0062685
SJK
23MAR10
CHECK
J A F
5 JUN 98
CHECK
5 JUN 98
DRAWN
DLT

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH

THIRD ANGLE PROJECTION

CHARACTERISTICS		ELECTRICAL DATA		SCALE FULL	
OPERATING FORCE-----6-12 LB		CONTACT ARRANGEMENT		DO NOT SCALE PRINT	
FULL OVERTRAVEL FORCE-----30 LB MAX		2X SPDT		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ONE PLACE (.0) ±.030 TWO PLACE (.00) ±.015 THREE PLACE (.000) ±.005 ANGLES ± WEIGHT 8 OZ MAX	
RELEASE FORCE-----4 LB MIN		28 VDC			
PRETRAVEL-----.040 MAX		LOAD	SEA LEVEL		50,000 FT.
DIFFERENTIAL TRAVEL-----.020 MAX		RES	5		
OVERTRAVEL-----.250 MIN		IND	3		
		MOTOR	4		
		LAMP			

ANSI Y14.5M-1982 APPLIES