



Sample image

<b>Order Symbol:</b>	<b>TPC 201610</b>
<b>Product Number:</b>	<b>5824001</b>
<b>Description:</b>	<b>Enclosure, PC</b>
<b>Remarks :</b>	<b>Grey Cover</b>
<b>Package:</b>	<b>4</b>
<b>Unit:</b>	<b>PCS</b>
<b>Product Group:</b>	<b>TEMPO</b>
<b>EAN:</b>	<b>6418074086648</b>
<b>ETIM:</b>	<b>EC000261</b>

Including: Base with PUR gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:	Length	Width	Height
<b>Inch:</b>	<b>7.9</b>	<b>6.4</b>	<b>3.9</b>
<b>MM:</b>	<b>201</b>	<b>163</b>	<b>98</b>

**Rating:**

NEMA Class: NEMA 1, 4, 4X, 12 Ingress Protection (EN 60529): IP65  
Impact Resistance (EN 62262): IK07/IK08  
Electrical insulation: Totally insulated  
Halogen free (DIN/VDE 0472, Part 815): 1  
Flammability Rating: UL 746C 5"  
Glow Wire Test (IEC 695-2-1) °C: 960

**Materials:**

**Material:** Polycarbonate  
**Base color:** RAL 7035 light grey  
**Cover screws material:** Polyamide  
**Cover color:** RAL 7035 light grey  
**Cover screw color:** Grey  
**Gasket material:** Polyurethane

**Certificates:**

SGS Fimko

**Accessories:**

MP 2016 Mounting plate

**Temperatures:**

**Temperature °C (short term):** -40 ... 120 °C  
**Temperature °C (continuous):** -40 ... 80 °C  
**Temperature °F (short term):** -40 ... 250 °F  
**Temperature °F (continuous):** -40 ... 175 °F

