



Sample image

<b>Order Symbol:</b>	<b>TPCM 201610</b>
<b>Product Number:</b>	<b>5824025</b>
<b>Description:</b>	<b>Enclosure, PC</b>
<b>Remarks :</b>	<b>Clear cover</b>
<b>Package:</b>	<b>4</b>
<b>Unit:</b>	<b>PCS</b>
<b>Product Group:</b>	<b>TEMPO</b>
<b>EAN:</b>	<b>6418074087171</b>
<b>ETIM:</b>	<b>EC000261</b>

Including: Base with metric knock-outs and PUR gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:	Length	Width	Height
<b>Inch:</b>	<b>7.9</b>	<b>6.4</b>	<b>3.9</b>
<b>MM:</b>	<b>201</b>	<b>163</b>	<b>98</b>

### Rating:

NEMA Class: NEMA 1, 4, 4X, 12  
 Ingress Protection (EN 60529): IP65  
 Impact Resistance (EN 62262): IK07/IK08  
 Electrical insulation: Totally insulated  
 Halogen free (DIN/VDE 0472, Part 815): 1  
 Flammability Rating: UL 746C 5"  
 Glow Wire Test (IEC 695-2-1) °C: 960

### Materials:

<b>Material:</b>	Polycarbonate
<b>Base color:</b>	RAL 7035 light grey
<b>Cover screws material:</b>	Polyamide
<b>Cover color:</b>	Clear
<b>Cover screw color:</b>	Grey
<b>Gasket material:</b>	Polyurethane

### Certificates:

SGS Fimko

### Accessories:

MP 2016 Mounting plate

### Temperatures:

<b>Temperature °C (short term):</b>	-40 ... 120 °C
<b>Temperature °C (continuous):</b>	-40 ... 80 °C
<b>Temperature °F (short term):</b>	-40 ... 250 °F
<b>Temperature °F (continuous):</b>	-40 ... 175 °F

