

MNX PC 150/75 HG



Sample photo

Order symbol: PC 150/75 HG
Product nbr: 6011314
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074022189
EI. number:
 Finland: 3420353
 Electric No. 8212022179
 Denmark:
 Electric No. Italy: 7351095
 Electric No. Sweden: 2535554

Including: Base with TPE gasket, screws for mounting plate/DIN-rail and cover with polyamide cover screws.

Dimensions:	Length	Width	Height	Accessories:
mm:	180	130	75	MIN 10 DIN-15 Mounting rail
inch:	7.1	5.1	3.0	MIN 15 DIN-15 Mounting rail

Materials:		
Material:	Polycarbonate	MIV 10 DIN-35 Mounting rail
Base colour:	RAL 7035 -light grey	MIV 15 DIN-35 Mounting rail
Cover screws material:	Polyamide	FP A 150/180 Front plate (Aluminium)
Cover colour:	RAL 7035 -light grey	HFP 180 Front plate hinge series
Cover screws colour:	Grey	FP 22046 Wall fastening lug (4 pcs)
Gasket material:	TPE	

Temperatures:		Rating:
Temperature °C (short term):	-40 ... 120 °C	Ingress Protection (EN 60529): IP66/IP67
Temperature °C (continuous):	-40 ... 80 °C	Impact Resistance (EN 62262): IK08
Temperature °F (short term):	-40 ... 250 °F	Electrical insulation: Totally insulated
Temperature °F (continuous):	-40 ... 175 °F	Halogen free (DIN/VDE 0472, Part 815): 1
		UV resistance: UL 508
		Flammability Rating: UL 746C 5"
		Glow Wire Test (IEC 695-2-1) °C: 960
		NEMA Class: NEMA 1, 4, 4X, 6

Accessories:		Certificates:
MIV 150	Mounting plate (Galvanized steel)	SGS Fimko

