

PICCOLO PC D 65 T



Sample photo

Order symbol: PC D 65 T
Product nbr: 8724007
Description: Enclosure, PC
Remarks: Transparent cover

EAN: 6418074002105
EI. number:
 Finland: 3423509
 Electric No. Denmark: 8212001569
 Electric No. Italy: 7202030
 Electric No. Sweden: 2536844

Including: Base with screws for mounting plate, cover with PUR gasket and polyamide cover screws.

| Dimensions: | Length | Width | Height | Accessories: | |
|-------------|--------|-------|--------|--------------|----------------------------|
| mm: | 170 | 80 | 65 | DH-3 | DIN-35 Mounting rail |
| inch: | 6.7 | 3.1 | 2.6 | FP 22040 | Wall fastening lug (2 pcs) |

| Materials: | | Rating: |
|-------------------------------|----------------------|--|
| Material: | Polycarbonate | Ingress Protection (EN 60529): IP66/IP67 |
| Base colour: | RAL 7035 -light grey | Impact Resistance (EN 62262): IK08 |
| Cover screws material: | Polyamide | Electrical insulation: Totally insulated |
| Cover colour: | Clear transparent | Halogen free (DIN/VDE 0472, Part 815): 1 |
| Cover screws colour: | Grey | UV resistance: UL 508 |
| Gasket material: | Polyurethane | Flammability Rating: UL 746C 5" |
| | | Glow Wire Test (IEC 695-2-1) °C: 960 |
| | | NEMA Class: NEMA 1, 4X, 6, 12, 13 |

| Temperatures: | | Certificates: |
|-------------------------------------|----------------|---------------|
| Temperature °C (short term): | -40 ... 120 °C | SGS Fimko |
| Temperature °C (continuous): | -40 ... 80 °C | |
| Temperature °F (short term): | -40 ... 250 °F | |
| Temperature °F (continuous): | -40 ... 175 °F | |

| Accessories: | |
|--------------|----------------|
| D-MP | Mounting plate |

